Key

1 One side of material must be open diffusion
2 Foils must not emit any releasing material or lubricant
3 Only for use as an aid to installation
4 For edge connections only

For external use

For internal use

Always use primer

		Bonding to and/or overlapping of…														Strip edge connections to … and/or between panel materials below																		Penetration by			
		Ampatop® Seal, roof membrane	**Ampatop® Aero**, roof membrane	**Ampatop® Protecta**, roof membrane	**Ampatop® Secura**, roof membrane	**Ampatop® F black**, wall membrane	**Sisalex® 30**, trickle protection paper	**Sisalex® 303**, vapour check	**Sisalex® 500**, vapour check	**Ampatex® DB 2 / DB 90**, vapour check	**Ampatex® Cento**, vapour check	**Ampatex® Resano®**, vapour check	**Sisalex® 514 / 518**, vapour barrier	**Sisalex® 871**, gas barrier	**Ampatex® SB 130 / Solero**, formwork strip	Polyethylene foils	Wood, planed, dry, dust-free	Raw wood	Soft wood fibre board	Medium-hard/medium density fibre board	Hard wood fibre board	OSB (sanded and un-sanded)	Chipboard	Cement-bonded chipboard	Gypsum wall board	Gypsum fibre board	Smooth, dust-free concrete	Rough, dust-free concrete	Dust-free brickwork and porous concrete	Grouting, mortar, plaster, etc.	Metals (aluminium, steel, etc.)	PE components (e.g. cladding)	PVC components (e.g. windows)	Bitumen, sanded strips	Vapour pipes, electrical conduits, cables	Wood (rafters, purlins, etc.)	Chimneys, ventilation pipes (steel)	Blow and installation openings
Acrylic adhesive tapes	**Ampacoll® XT, 60 mm**	weldable	✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔[2]	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔		✔	✔	✔	✔	✔	✔				
	Ampacoll® XT, 60 mm, double slit		✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔[2]	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔		✔	✔	✔	✔	✔	✔				
	Ampacoll® XT, 75/100/150 mm		✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔[2]	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔				
	Ampacoll® UV, 60 mm					✔																															
	Ampacoll® AT, 50 mm						✔	✔	✔	✔	✔		✔	✔		✔[2]	✔			✔	✔	✔	✔	✔	✔	✔					✔	✔	✔					
	Ampacoll® INT, 60 mm						✔	✔	✔	✔	✔		✔			✔[2]	✔					✔	✔	✔	✔	✔					✔	✔	✔		✔			
	Ampacoll® Profix, 150 mm						✔	✔	✔	✔	✔		✔			✔[2]	✔					✔	✔	✔	✔	✔					✔	✔	✔					✔
	Ampacoll® FE, 60 mm						✔	✔	✔	✔	✔	✔	✔			✔[2]	✔														✔	✔	✔					
	Ampacoll® DT, 20 mm						✔[3]	✔[3]	✔[3]	✔[3]	✔[3]	✔[3]	✔[3]			✔[2,3]	✔														✔	✔	✔					
Adhesive compounds	**Ampacoll® Superfix**[1]		✔	✔		✔						✔	✔[4]		✔[4]	✔[4]	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔				
	Ampacoll® RA[1]						✔[4]	✔[4]	✔[4]	✔[4]	✔[4]		✔[4]	✔[4]	✔[4]	✔[4]	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔		✔	✔	✔				
Butyl tapes	**Ampacoll® RS, 4 mm**																✔													✔	✔	✔					
	Ampacoll® RS, 6/10/20 mm																✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔				
	Ampacoll® BK 530, 1 x 15 mm						✔	✔	✔	✔	✔		✔		✔		✔													✔	✔	✔					
	Ampacoll® BK 530, 2 x 20 mm						✔	✔	✔	✔	✔			✔			✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔				
	Ampacoll® BK 535		✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	
	Ampacoll® F		✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	
	Ampacoll® BKF		✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	
Primer	**Ampacoll® Connecto**		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔			✔	✔	✔	✔	✔	✔
Nail seals	**Ampacoll® ND**		✔	✔	✔										✔				✔	✔																		
Nail sealing tape	**Ampacoll® ND.Band**	✔	✔	✔	✔										✔				✔	✔																		
	Ampacoll® ND Duo	✔	✔	✔	✔										✔		✔	✔	✔	✔																		
Sleeves	**Ampacoll® Elektro and Install**		✔	✔	✔		✔	✔	✔	✔	✔	✔	✔	✔	✔	✔[2]	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔	✔				

The above data should be treated as recommended for the best possible use of our materials. **Make sure that the relevant product data sheets are adhered to.** If you have any questions, Ampack is glad to help. Based on our experience and recommendations made in national standards, a mechanical backup should be used when working around joints. In many cases, the internal panel performs this role. If in doubt, use primer or carry out your own adhesion tests. In order to obtain proper bonding and thus sustainable wind and air-tight layers, the surfaces to be bonded should be clean, dry, and free of dust and grease. Permanent exposure to the weather or to moisture can permanently impair bonding or make it unusable.